

















POWER[®]pack

STUFFING BOX PACKINGS CHEMICAL RESISTANCE

	water	steam	neutral solutions	highly diluted acids	concentrated acids	highly concentrated acids	diluted alkalis	concentrated alkalis	inert gas	acidic gas	hydrogen	oxygen	volatile hydrocarbon	solvents	amines, nitriles	mineral oils	synthetic oils	abrasive media	bitumen	paints, varnishes
 1010	■	■	■	■	■	▣	■	■	■	■	▣	▣	■	■	■	■	■	◇	◇	■
 1010-I	■	■	■	■	■	▣	■	■	■	■	▣	▣	■	■	■	■	■	◇	◇	■
 1020	■	■	■	■	■	▣	■	■	■	■	▣	▣	■	■	▣	■	■	▣	◇	■
 1110	■	■	■	■	■	▣	■	■	■	■	◇	◇	■	■	◇	■	■	◇	◇	■
 1210	■	■	■	■	■	▣	■	■	■	■	◇	◇	■	■	▣	■	■	◇	◇	■
 1410	■	■	■	■	▣	◇	▣	◇	■	▣	◇	◇	■	■	◇	■	■	◇	◇	■
 3010	■	■	■	■	■	■	■	■	■	■	■	◇	■	■	■	■	■	▣	▣	◇
 3020	■	■	■	■	▣	◇	■	◇	■	▣	▣	◇	▣	■	■	■	■	■	■	◇
 3010-S ◆																				
 3010-V ◆																				
 4010	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	▣	▣	■
 4020	■	■	■	■	■	■	■	■	■	■	▣	◇	■	■	■	■	■	▣	▣	■
 4020-S ◆																				
 4020-V ◆																				
 5010	■	■	■	▣	◇	◇	■	◇	■	◇	▣	◇	▣	■	◇	■	■	■	■	■
 5510	■	▣	■	■	◇	◇	■	◇	■	◇	▣	◇	▣	▣	◇	■	◇	◇	◇	◇
XXXX	Ucpávky z jiných druhů materiálů na poptávku.																			

■ recommended ▣ limited usability ◇ not recommended ◆ limited usability according to flexible core material



Pokorný, spol. s r. o.
Pod sídlištěm 1, 636 00 Brno
Czech Republic
tel.: +420 548 321 534
fax: +420 548 216 240
e-mail: pokorny.office@tesneni.cz

All datas are based on our measurements and our experience and are only informative. All parameters stated are subject of interaction and in limit applications have to be consulted. The manufacturer is not responsible for a wrong datas interpretation and a wrong gasket application. All datas and informations are an intellectual property of co. Pokorný, Ltd. Any reproduction, copying, and using the datas from this catalogue are subject of co. Pokorný, Ltd. approval.

www.seals.cz



ISO 9002